



PRE-RACE SAFETY CHECKLIST

- 1. NUMBERS** ... Must be black on white or white on black and **MUST LOOK LIKE THE EXAMPLES!** IF YOUR NUMBERS DO NOT LOOK LIKE THESE EXAMPLES **DO NOT EXPECT TO BE CLEARED AT TECH.** YOU WILL HAVE TO CORRECT THEM BEFORE YOU WILL BE ALLOWED TO RACE. Number sizes are as follows; 4" front on visor area, 8" side numbers (one on each side), one 6" rear facing.

1234

1234

- 2. LIGHTS** ... Rear facing lights are as follows; 2 Brake/tail lights, 1 Amber, 1 Blue for vehicles racing limited laps. Brake lights must be only connected to pedal brake switch "no hand controlled switch." **Amber lights must be wired to the ignition switch.** Tail lights must operate with instrument lights or a set of headlights "must not be on a separate switch." Rear-facing brake/tail lights must be on during entire night event or races that extend into the night hours. Amber and Blue lights **MUST** be connected to ignition switch and **must BOTH be on entire event and must be repaired if stopped at a checkpoint.** Blue light classes are as follows: 3, 4, 5-1600, 6, 7, 7s, Mini Metal, 9, 13, 15, 18, 1450, Stock Bug. Stock Bug must use a blue Kartek strobe 6" oval light, part #FSC 60710103 or equivalent.
- 3. HARNESES** ... Must be NO older than 3 years from date on belts. Two single shoulder harnesses are required, NO V or Y type shoulder type. Double "D" rings are required. If harnesses are clip-on type, they **MUST** be safety wired. NO twist type latches...must be a lever latch type release.
- 4. FIREWALLS** ... Buggies only (trucks have fuel cell in rear). Vent line for fuel cell must run to top of roll cage, to the other side, then down to the floor
- 5. FIRE EXTINGUISHER** ... required 2.5 pound "A-B-C" rated.
- 6. HORNS** ... All vehicles must have a horn that works.
- 7. REARVIEW MIRROR...** **All vehicles must have a rearview or side mirrors!**
- 8. FIRST AID** ... Must have first aid supplies in it. **NO TOOLS OR OTHER ITEMS!**
- 9. TRIANGLE** ... Reflective triangle is mandatory.
- 10. HELMETS** ... a SNELL approved helmet SA or M 2000 or SA or M 2005 w/SNELL label affixed to the helmet. Also acceptable is 2005 ECE-22 with BSI label attached.
- 11. DRIVING SUITS** ... Are mandatory! Must be a one (1) piece suit that covers from the neck to the ankles. **NO HOLES OR TEARS!** (including catheter holes or cooling tubes).
- 12. FUEL LINES...** Hose clamps on all fuel lines, even if they are push lock. **NO EXCEPTIONS.**
- 13. NETS** ... Must cover from "A" pillar to "B" pillar.....from top "roof" to bottom "top of body Panel. Must have steel clamps.
- 14. DRIVE SHAFT** ... Drive shaft safety loop **is required on all vehicles with a drive shaft.** Retainer loop could be made of .25" x 2" steel or 2" wide nylon webbing, both securely bolted to frame.
- 15. CARBURETOR SPRINGS** ... double throttle return springs.

**PLEASE CONTACT BILL SHAPLEY WITH ANY QUESTIONS
(702) 438-4689**